

Product information

WISI MK 15 0500

Coaxial cable, black



Description

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern-Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 28. Januar 2015, 3:15 nachm.

Technical data

Installation	wet room
Screening construction	3-way
Inner conductor material	Cu-core
Dielectric	Cell PE/copper braiding MK 15 + Al-foil
Outer conductor material	Bonded aluminium foil / copper braid
Outer jacket material	PE
Inner conductor diameter	1.63 mm
Dielectricum diameter	7.2 mm
Outer jacket diameter	10.3 mm
Loop resistance	16 Ω /km
Loss 5 MHz	0.9 dB (100m)
Attenuation 50 MHz	2.8 dB (100m)
Attenuation 600 MHz	10.1 dB (100m)
Attenuation 1000 MHz	13.1 dB (100m)
Loss 2200 MHz	20.7 dB (100m)
Return loss 5...862 MHz	>28 dB
Return loss 862...2500 MHz	>23 dB
Screening factor (EMC)	>100 dB
Coupling resistance	<1 m Ω /m

General data

color	black
Cable weight	76 kg/km
Bending radius	100 mm
classification	Class A

Packaging data

Sales unit	500 m (wood drum)
Gross weight shipping unit	0.076 kg
EAN	4010056149017
Article number	14901
Customs tariff number	85442000
Sales unit	500 pcs.