

WISI OH 40 A

Compact Headend basic unit, 230 V AC, 19", 3 HE, for 7 modules



Description

At a glance:

- Slots for up to 7 modules
- Wall mounting
- Integrated FM amplifier
- Programable with OH 41 hand-set
- Update via USB-connection (USB memory stick)
- Integrated remote supervision moduel OH 51 A (license optional)

WISI Communications GmbH & Co. KG

Wilhelm-Sihn-Str. 5-7
75223 Niefern - Oeschelbronn, Germany

Phone: +49 7233 66-280, Fax: -350
E-Mail: export@wisi.de

Technical Modifications reserved. WISI cannot be held liable for any printing error. 25. März 2015, 3:53 nachm.

Technical data

Frequency range TV	47...862 MHz (output combiner/ amplifier)
Frequency range FM	87,5...108 MHz (FM-amplifier)
Input level FM	70...100 dB μ V
Gain FM	25 dB
Attenuator FM	0...30 dB (1 dB-steps)
Output level	110 dB μ V
Output attenuator	0...15 dB
Output test point	-20 dB

Connectors

Module slots	7 pcs. (OH-module)
F-socket	3 pcs. (FM-input, output, output measurement socket)
USB	1 pcs. (Software-Update, Konfiguration)
RJ11	1 pcs. (OH 41)
RJ45	1 pcs. (remote monitoring and programming)

General data

Operating voltage AC	180...265 V
Power consumption	<185 W
LNB supply voltage	12.5 V
LNB electrical power supply	1.2 A
Dimensions (width x height x depth)	276x159x385 mm
Operating temperature range	-20...+50 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
	dm ³
Gross weight sales unit	kg
Shipping unit	m
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	23.5 dm ³
Gross weight shipping unit	5.45 kg
	cm
	N
EAN	4010056731441
Article number	73144
Customs tariff number	85437090
Country of origin	