

WISI OH 50 A

Compact Headend basic unit, 230 V AC, 19", 3 HE, for 14 modules



Description

At a glance:

- Base unit OH 50 for analog und digital channel processing headends
- Slots for up to 14 modules (14 analog or 28 digital channels)
- 19" rack-mounting or wall mounting
- Integrated FM amplifier
- Simple programming with handset OH 41 (OK 41 A)
- Preprogramming via USB-connection (USB-Stick)
- Integrated remote supervision moduel OH 51 A (license optional)
- High output power

Technical data

Frequency range TV	47...862 MHz (output combiner/ amplifier)
Frequency range FM	87,5...108 MHz (FM-amplifier)
Input level FM	70...100 dB μ V
Gain FM	25 dB
Attenuator FM	30 dB (1 dB-steps)
Output level	110 dB μ V
Output attenuator	0...15 dB
Output test point	-20 dB

Connectors

Module slots	14 pcs. (OH-module)
F-socket	3 pcs. (FM-input, output, output measurement socket)
USB	1 pcs. (Software-Update, Konfiguration)
RJ11	1 pcs. (OH 41)
RJ45	1 pcs. (remote monitoring and programming)

General data

Operating voltage AC	180...265 V (47...63 Hz)
Power consumption	<185 W
LNB supply voltage	12.5 V
LNB electrical power supply	1.2 A
Dimensions (width x height x depth)	443x132x351 mm (3 HE)
Operating temperature range	-20...+50 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	mm
	dm ³
Gross weight sales unit	kg
Shipping unit	m
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	31.5 dm ³
Gross weight shipping unit	7.64 kg
	cm
	N
EAN	4010056730116
Article number	73011
Customs tariff number	85437090
Country of origin	